










<http://triangleart.net/>

Фото	Модель	Описание	Цена, долл
	<b>ULTIMATE LE</b>	Gold/ Chrome Metal composite turntable AC motor drive with Crystal Digital Technology speed controller Platter: Chrome polished composite metal 229 mm thick Motor: 1 motor mounted into chassis Non-Inverted hydro dynamic oil fed bearing Up to 2 tonearms can be mounted Dimensions: 45 H x 22 W x 20-1/2 D Weight: 850 LBS	<b>\$154 800</b>
	<b>MASTER REFERENCE</b>	Nickel and Chrome Composite metal plate Double 80 mm platter Resonance and optimized vibration. Possible install 2 tonearm External Crystal Digital Controller External AC motor tower Speed range 33.3 and 45 RPM Voltage: 120-240V 50/60Hz	<b>\$47 880</b>
	<b>REFERENCE SE</b>	Gold/Chrome plating One Arm base of your choice Can Mounted 9" to 12" tonearm External AC Motor With housing External Crystal Digital Speed Controller 33 and 45 RPM speed Available in Black or Gold color	<b>\$34 200</b>
	<b>SIGNATURE SE</b>	Chrome Plating One Arm base of your choice External AC Motor With housing External Crystal Digital Speed Controller External tone arm tower 33 and 45 RPM speed Available in Chrome, Gold, Red and Black	<b>\$23 988</b>
	<b>MAESTRO</b>	Dimensions: 18L x 17D x 10H Weight: 80 LBS AC motor with stabilizer for 33/45 speed Controller motor drive is optional	<b>\$11 250</b>
	<b>CONCERTO</b>	Chrome metal composite turntable AC motor 115V/60hz or 240V/50hz Platter: Chrome polished composite metal 25mm External Chrome Metal composite motor tower External Chrome Metal Composite tone arm tower 1 Jelco SA750 tonearm and SA501 phono cables Dimension 8" H x 16 W x 16 D Weight: 40 LBS Non-Inverted hydro dynamic oil fed bearing Up to 2 tonearms can be mounted Option: External Controller drive	<b>\$6 300</b>
		Option Base 20" x 20" x 1"	<b>\$1 620</b>
		***CONCERTO and HORUS TONEARM special package price	<b>\$9 600</b>
	<b>APOLLO MC ONXY STONEBODY</b>	Type: Moving Coil (Dynamic) Output Voltage: 0.3mV (3.54cm/sec,1KHz) Frequency Response: 10Hz-50KHz Channel Separation: 30dB (1KHz) Channel Balance: 0.5dB (1KHz) Tracking Force: 2.0 gr (20°C-25°C) Trackability: 70°m / 2.0gr Compliance: 12 x10-6cm / dyne Internal Impedance: 4 OHM Load Impedance: 100 OHM Coil Wire: Special Copper Cantilever Material : Boron solid / 0.28mm Stylus: Micro-Ridge Solid Diamond Contact Radius: 3°m x 70°m Net Weight: 11gr	<b>\$10 500</b>

Цена указана по состоянию на 01.07.2018г., может быть изменена, в зависимости от колебаний курса валют.  
Дополнительные опции - по запросу.

[www.orion7.com.ua](http://www.orion7.com.ua)













Фото	Модель	Описание	Цена, долл
	<b>ZEUS MC CARTRIDGE</b>	Type Moving Coil (Dynamic) Output Voltage 0.3mV (3.54cm/sec,1KHz) Frequency Response 10Hz-50KHz Channel Separation 30dB (1KHz) Channel Balance <0.5dB (1KHz) Tracking Force 2.0 gr (20°C-25°C) Trackability >70°m / 2.0gr Compliance 12 x10-6cm / dyne Internal Impedance 4? Load Impedance >100? Coil Wire 6N Copper with acryo Cantilever Material Boron solid / 0.28mm Stylus Micro-Ridge Solid Diamond	<b>\$4 794</b>
	<b>OSIRIS MKII TONEARM</b>	9" Makassae Ebony Tone arm 12" Makassar Ebony Tone arm Brass construction housing Single point magnetic bearing Effective tone arm length 9- 229mm Effective tone arm length 12" - 304mm Direct Crystal Clear 99.9% Pure Silver wire	<b>\$7 470</b> <b>\$8 370</b>
	<b>HORUS TONEARM</b>	9" Makassae Ebony Tone arm 12" Makassar Ebony Tone arm Aluminum construction housing Unipivot bearing with Diamond carbon coding Direct Crystal Clear 99.9% pure silver wire	<b>\$3 960</b> <b>\$4 440</b>
	<b>REFERENCE TUBE MONO BLOCK AMPLIFIER</b>	Pure Class A design Rated Power Output: 160 Watts RMS Input Sensitivity: 1V RMS for rated output Input Impedance: 100K Ohms Frequency Response: -0.5 dB from 20 Hz to 20000 Hz -3.0 dB from 8 Hz to 80,000 Hz THD: 1% S/N Ratio: 110 dB Damping Factor: >14 Power Consumption: 300 Watts Output Impedance: 4, 8 Ohm Tube Complement (per monoblock): 4-KT88 2-6SN7 Dimensions (per monoblock): 13.75" W x 20.25" D x 8.5" H Weight (per amplifier): 50 lbs.	<b>\$21 600</b>
	<b>REFERENCE TUBE 2 CHASSIS PREAMPLIFIER WITH REMOTE CONTROL</b>	Low noise tube line stage featuring (4) 6SN7 vacuum tubes. Matching external power supply featuring (1)GZ34, (2) 6V6 and (1) 6SL7 vacuum tubes. Rectifier with double choke filtering (two chokes are employed). Custom EI power transformers. Swiss made ELMA selector switches with gold-plated contacts. Amtrans AMRG premium carbon film resistors with gold-plated leads. Four pairs of single-ended inputs and two pairs of outputs are installed for ease of connectivity.	<b>\$22 800</b>
	<b>REFERENCE TUBE PHONO STAGE</b>	Gain at 1 kHz – Moving Magnet: 48.5 dB - Moving Coil: 69.5 dB Frequency Response: +/- 0.25 dB from 20 Hz to 22k Hz (RIAA Equalized) THD – Moving Magnet: < 0.06% at 0.5V RMS 1kHz output - Moving Coil: < 0.03% at 0.5V RMS 1kHz output Signal to Noise Ratio – Moving Magnet: 85 dB, A weighted - Moving Coil: 80 dB, A weighted Tube Complement – LINE STAGE: 4 – 12AX7 Tube Complement – POWER SUPPLY: 1 – 5AR4, 1 – 6SL7, 1 – 6V6	<b>\$15 600</b>
	<b>TA 260 S</b>	Rated Output Power: 250 Watts RMS at 8 Ohms 500 Watts RMS at 4 Ohms Frequency: +/- 0.1 dB from 10 Hz to 50 kHz Signal-to-Noise Ratio: 110 dB Total Harmonic Distortion (THD): <0.014% Gain: 28 dB Input Impedance: 35K Ohms (single-ended) 50K Ohms (balanced) Input Sensitivity: 1.75 V RMS Output Voltage: 50 V RMS Damping Factor: 250, referred to 8 ohms Power Consumption: 700 watts continuous Inputs: 2 balanced via XLR connector (1 per channel) 2 single-ended via RCA connector (1 per channel) Outputs: 2 pairs high quality Mundorf MConnect binding posts (1 pair per channel) Operating Voltage: 100V, 120V, 220V, 230V or 240V at 50 or 60 Hz Dimensions: 19 in. W x 9.25 in. H x 23 in. D Weight: 128 lbs. Warranty: 2 Years Parts and Labor	<b>\$24 000</b>

Фото	Модель	Описание	Цена, долл
	<b>RHEA REFERENCE INTERCONNECT</b>	RCA or XLR ( BALANCED) Standard 1.5 Meter Carbon Fiber Connector with Rhodium Carbon Fiber Shielding Pure Silver with Rhodium Plated	<b>\$2 970</b>
		*5 Meter Additional	<b>\$1 050</b>
	<b>RHEA REFERENCE SPEAKER CABLE</b>	Standard 2-Meter Carbon Fiber Connector with Rhodium Carbon Fiber Shielding Pure Silver with Rhodium Plated	<b>\$4 950</b>
		*5 Meter Additional	<b>\$1 500</b>
	<b>RHEA REFERENCE POWERCORD</b>	Standard 2-Meter Carbon Fiber Connector with Rhodium Carbon Fiber Shielding Pure Silver with Rhodium Plated	<b>\$2 970</b>
		*5 Meter Additional	<b>\$1 050</b>
	<b>CRYSTAL DIGITAL CONTROLLER</b>	External Controller drive	<b>\$3 600</b>
	<b>TA-1 RECORDS CLAMP</b>	TA-1 Records clamp stations solidly upon the turntable keeping the long-play disc in place and improving listener focus on three dimensional sound stage. its tightly controlled low frequency bass construction is non-vibrating and more stable	<b>\$1 620</b>