

















<b>Item</b>	<b>Description</b>	<b>Photo</b>	<b>Euro / pc</b>
<b>KR PX-25</b>	Maximum Plate Voltage 500 V Maximum Plate Current 90 mA Plate Dissipation 30 Watts Va 400 V Ia 63 mA Vg -31 V Transconductance 7.4 mA/V Amplification Factor 9.5 Filament Voltage 4 V (DC/AC) Filament Current 1.8 A		594
<b>KR 300B</b>	Maximum Plate Voltage 550 V Maximum Plate Current 120 mA Plate Dissipation 50 Watts Va 450 V Ia 100 mA Vg -90 V Transconductance 6.2 mA/V Amplification Factor 3.9 Filament Voltage 5 V (DC/AC) Filament Current 1.2 A		585
<b>KR 300B Balloon</b>	Maximum Plate Voltage 550 V Maximum Plate Current 120 mA Plate Dissipation 50 Watts Va 450 V Ia 100 mA Vg -90 V Transconductance 6.2 mA/V Amplification Factor 3.9 Filament Voltage 5 V (DC/AC) Filament Current 1.2 A		630
<b>KR 842VHD</b>	Maximum Plate Voltage 600 V Maximum Plate Current 150 mA Plate Dissipation 65 Watts Va 450 V Ia 100 mA Vg -94 V Transconductance 5.7 mA/V Amplification Factor 3.7 Filament Voltage 5 V (DC/AC) Filament Current 1.8 A		690
<b>KR 300BLXS</b>	Maximum Plate Voltage 600 V Maximum Plate Current 160 mA Plate Dissipation 70 Watts Va 450 V Ia 100 mA Vg -94 V Transconductance 5.7 mA/V Amplification Factor 3.7 Filament Voltage 5 V (DC/AC) Filament Current 1.8 A		690

<p><b>KR 845 M</b></p>	<p>Maximum Plate Voltage 1250 V  Maximum Plate Current 140 mA  Plate Dissipation 100 Watts  Va 650 V  Ia 90 mA  Vg -68 V  Transconductance 3.0 mA/V  Amplification Factor 5.5  Filament Voltage 10 V (DC/AC)  Filament Current 1.0 A</p>		<p>855</p>
<p><b>KR T100</b></p>	<p>Maximum Plate Voltage 1000 V  Maximum Plate Current 140 mA  Plate Dissipation 100 Watts  Va 650 V  Ia 90 mA  Vg -87 V  Transconductance 4.4 mA/V  Amplification Factor 5.3  Filament Voltage 5 V (DC/AC)  Filament Current 2.0 A</p>		<p>855</p>
<p><b>KR 211</b></p>	<p>Maximum Plate Voltage 1250 V  Maximum Plate Current 140 mA  Plate Dissipation 100 Watts  Va 650 V  Ia 90 mA  Vg -15 V  Transconductance 4.0 mA/V  Amplification Factor 12  Filament Voltage 10 V (DC/AC)  Filament Current 1.0 A</p>		<p>735</p>
<p><b>KR PX-4</b></p>	<p>Maximum Plate Voltage 350 V  Maximum Plate Current 60 mA  Plate Dissipation 20 Watts  Va 250 V  Ia 48 mA  Vg -32 V  Transconductance 5.1 mA/V  Amplification Factor 5.0  Filament Voltage 4 V (DC/AC)  Filament Current 1.1 A</p>		<p>615</p>
<p><b>KR T1610</b></p>	<p>Maximum Plate Voltage 650 V  Maximum Plate Current 250 mA  Plate Dissipation 150 Watts  Va 400 V  Ia 160 mA  Vg -83 V  Transconductance 9.9 mA/V  Amplification Factor 3.7  Filament Voltage 5 V (DC/AC)  Filament Current 3.8 A</p>		<p>2850</p>
<p><b>Marconi "R"  Valve™</b></p>	<p>Maximum Plate Voltage 180 V  Maximum Plate Current 2 mA (Vf=4V,Vg=0V)  Va 120 V  Ia 1 mA  Vg -0.5 V  Transconductance 0.3 mA/V  Filament Voltage 4 V (DC/AC)  Filament Current 0.6 A</p>		<p>360</p>

<p><b>KR 2A3</b></p>	<p>Maximum Plate Voltage 300 V  Maximum Plate Current 100 mA  Plate Dissipation 15 Watts  Va 250 V  Ia 70 mA  Vg -45 V  Transconductance 5.2 mA/V  Amplification Factor 3.8  Filament Voltage 2.5 V (DC/AC)  Filament Current 2.5 A</p>		<p>465</p>
<p><b>KR 274 B/A, 5U4G</b></p>	<p>KR 274: DC/AC Voltage 5 V  DC/AC Current 2 A Maximum Ratings  With Choke-Input Filter:  A-C Plate Voltage per Plate (RMS) 660 volts  D-C Output Current 225 ma  Minimum Input-Choke Inductance 2 henrys  With Capacitor-Input Filter:  A-C Plate Voltage per Plate (RMS) 450 volts  D-C Output Current 160 ma  Min. Total Eff. Plate-Supply Impedance per Plate 100 ohms  Input capacitor should not exceed 10 micro farads. KR  5U4G With Choke-Input Filter  A-C Plate Voltage per Plate (RMS) 550 Volts  D-C Output Current 225 mA  Minimum Input-Choke Inductance 3 henrys  With Capacitor-Input Filter  A-C Plate Voltage per Plate (RMS) 450 Volts  D-C Output Current 225 mA  Min. Total Eff. Plate-Supply Impedance per Plate 75 ohms  Input capacitor should not exceed 10 micro farads</p>		<p>546</p>
<p><b>KR 5</b></p>	<p>Maximum Plate Voltage 600 V  Maximum Plate Current 50 mA  Plate Dissipation 20 Watts  Va 400 V  Ia 50 mA  Vg -10 V  Transconductance 3 mA/V  Amplification Factor 18  Filament Voltage 6.3 V (DC/AC)  Filament Current 0.9 A</p>		<p>390</p>
<p><b>KR242</b></p>			<p>600</p>
<p><b>KR3A</b></p>			<p>540</p>
<p><b>KR45</b></p>			<p>450</p>